

leboulch

ADVANTAGE SERIES

GOLIATH 54S15

ADGO54S15/1-20



Non-contractual photo

ADVANTAGE
SERIES

- ✓ Narrow monocoque muck spreader with monoblock rounded side walls and large wheels, manufactured in special steel.
- ✓ Muck spreader designed for a technically permissible payload of 12 t and a manure volume of 15.2 m³.
- ✓ 2K industrial paint and finishing lacquer.
- ✓ ADR 130x2200-10S axle with 406 x 120 mm hydraulic brakes.
- ✓ Wheels 650/75R32 (Mitas) AC70F 172 A8 (Ø 1,795 mm x 650 mm, 6,300 kg per wheel at 40 km/h)
- ✓ Spring loaded boom drawbar for maximum comfort and stability when rolling.
- ✓ 1,000 rpm drive by homocinetic P.T.O.-shaft with cam security (beater rotation speed: 430 rpm).
- ✓ Two Ø 16 mm shipping chains with mechanical tensioners.
- ✓ 2 vertical beaters with removable coupling and regular spirals (Ø 900 mm, 10-mm thick reinforced steel), removable blades on wear ring and spoon knives (1/2).
- ✓ Reversible and interchangeable HARDOX blades (10 mm)
- ✓ Hydraulic tensioning of the moving floor with under-tension security and RE mode locking.
- ✓ Bolted rectangular slats of moving floor (80 x 40).
- ✓ Hydraulic guillotine door with electric control.
- ✓ Galvanised side boards.
- ✓ LB300 control box with reverse, moving floor speed and door control.
- ✓ Independent hydraulic installation.
- ✓ Mechanically welded steel gearwheels.
- ✓ Reinforced reduction gearbox for single-speed moving floor.
- ✓ Hydraulic stand.
- ✓ Protected carter.
- ✓ Protected lights folding automatically with moving floor drive.
- ✓ 2020 certification.
- ✓ Easy maintenance and cleaning. Machine delivered with its spare parts book to make the replacement of wear parts easier.
- ✓ Industrial manufacturing in large series, continuous welds.
- ✓ 3-year warranty (see terms)



Other Advantage series on:

www.leboulch.com/advantage